

Appendix H

Existing Traffic Analysis

HCM Unsignalized Intersection Capacity Analysis
1: Winston Churchill Boulevard & Olde Base Line Road

Existing Traffic
AM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	WBL	WBR	NBT	NBR	SBL	SBT
Volume (veh/h)	8	31	13	21	158	40
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	8	31	13	21	158	40
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None		None	
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	380	24			34	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	380	24			34	
tC, single (s)	6.4	6.3			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.4			2.2	
p0 queue free %	99	97			90	
cM capacity (veh/h)	564	1030			1584	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	39	34	198			
Volume Left	8	0	158			
Volume Right	31	21	0			
cSH	881	1700	1584			
Volume to Capacity	0.04	0.02	0.10			
Queue Length 95th (m)	1.0	0.0	2.3			
Control Delay (s)	9.3	0.0	6.2			
Lane LOS	A		A			
Approach Delay (s)	9.3	0.0	6.2			
Approach LOS	A					
Intersection Summary						
Average Delay			5.8			
Intersection Capacity Utilization		27.5%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
2: Winston Churchill Boulevard & Sideroad 5

Existing Traffic
AM Peak Hour

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Volume (veh/h)	4	42	6	38	152	1
Sign Control	Stop			Free	Free	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	4	42	6	38	152	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type				None	None	
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	202	152	153			
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	202	152	153			
tC, single (s)	6.4	6.2	4.1			
tC, 2 stage (s)						
tF (s)	3.5	3.3	2.2			
p0 queue free %	99	95	100			
cM capacity (veh/h)	787	899	1440			
Direction, Lane #	EB 1	NB 1	SB 1			
Volume Total	46	44	153			
Volume Left	4	6	0			
Volume Right	42	0	1			
cSH	888	1440	1700			
Volume to Capacity	0.05	0.00	0.09			
Queue Length 95th (m)	1.1	0.1	0.0			
Control Delay (s)	9.3	1.1	0.0			
Lane LOS	A	A				
Approach Delay (s)	9.3	1.1	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			1.9			
Intersection Capacity Utilization		18.1%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
3: Winston Churchill Boulevard & The Grange Side Road

Existing Traffic
AM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	2	3	52	4	6	149
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	2	3	52	4	6	149
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	215	54			56	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	215	54			56	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	775	1019			1562	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	5	56	155			
Volume Left	2	0	6			
Volume Right	3	4	0			
cSH	905	1700	1562			
Volume to Capacity	0.01	0.03	0.00			
Queue Length 95th (m)	0.1	0.0	0.1			
Control Delay (s)	9.0	0.0	0.3			
Lane LOS	A		A			
Approach Delay (s)	9.0	0.0	0.3			
Approach LOS	A					
Intersection Summary						
Average Delay			0.4			
Intersection Capacity Utilization		22.7%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
4: Winston Churchill Blvd & Bush Street

Existing Traffic
AM Peak Hour



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑ ↗			↖ ↘	↖ ↗	
Volume (veh/h)	107	139	2	52	54	12
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	107	139	2	52	54	12
Pedestrians					2	
Lane Width (m)					3.7	
Walking Speed (m/s)					1.2	
Percent Blockage					0	
Right turn flare (veh)						
Median type	None		None			
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume		248		234	178	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol		248		234	178	
tC, single (s)		4.1		6.5	6.2	
tC, 2 stage (s)						
tF (s)		2.2		3.6	3.3	
p0 queue free %		100		93	99	
cM capacity (veh/h)		1327		736	868	
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	246	54	66			
Volume Left	0	2	54			
Volume Right	139	0	12			
cSH	1700	1327	757			
Volume to Capacity	0.14	0.00	0.09			
Queue Length 95th (m)	0.0	0.0	2.0			
Control Delay (s)	0.0	0.3	10.2			
Lane LOS		A	B			
Approach Delay (s)	0.0	0.3	10.2			
Approach LOS			B			
Intersection Summary						
Average Delay			1.9			
Intersection Capacity Utilization		24.7%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
5: Olde Base Line Road & Shaws Creek Road

Existing Traffic
AM Peak Hour



Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Volume (veh/h)	2	173	50	3	4	1
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	2	173	50	3	4	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	53			228	52	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	53			228	52	
tC, single (s)	4.1			6.4	6.2	
tC, 2 stage (s)						
tF (s)	2.2			3.5	3.3	
p0 queue free %	100			99	100	
cM capacity (veh/h)	1566			763	1022	
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	175	53	5			
Volume Left	2	0	4			
Volume Right	0	3	1			
cSH	1566	1700	804			
Volume to Capacity	0.00	0.03	0.01			
Queue Length 95th (m)	0.0	0.0	0.1			
Control Delay (s)	0.1	0.0	9.5			
Lane LOS	A		A			
Approach Delay (s)	0.1	0.0	9.5			
Approach LOS			A			
Intersection Summary						
Average Delay			0.3			
Intersection Capacity Utilization		20.7%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
6: Rockside Road & Olde Base Line Road

Existing Traffic
AM Peak Hour



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑			↑	↑	
Volume (veh/h)	178	1	1	35	2	4
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	178	1	1	35	2	4
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None		None			
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume		179		216	178	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol		179		216	178	
tC, single (s)		4.1		6.4	6.2	
tC, 2 stage (s)						
tF (s)		2.2		3.5	3.3	
p0 queue free %		100		100	100	
cM capacity (veh/h)		1409		777	870	
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	179	36	6			
Volume Left	0	1	2			
Volume Right	1	0	4			
cSH	1700	1409	836			
Volume to Capacity	0.11	0.00	0.01			
Queue Length 95th (m)	0.0	0.0	0.2			
Control Delay (s)	0.0	0.2	9.3			
Lane LOS		A	A			
Approach Delay (s)	0.0	0.2	9.3			
Approach LOS		A				
Intersection Summary						
Average Delay		0.3				
Intersection Capacity Utilization		19.4%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
7: Mississauga Road & Olde Base Line Road

Existing Traffic
AM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	0	49	141	7	24	7	13	40	9	15	199	2
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	0	49	141	7	24	7	13	40	9	15	199	2
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	320	305	200	466	302	44	201			49		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	320	305	200	466	302	44	201			49		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.2			4.2		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.3			2.3		
p0 queue free %	100	92	83	98	96	99	99			99		
cM capacity (veh/h)	604	597	843	392	596	1031	1342			1533		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	190	38	62	216								
Volume Left	0	7	13	15								
Volume Right	141	7	9	2								
cSH	762	586	1342	1533								
Volume to Capacity	0.25	0.06	0.01	0.01								
Queue Length 95th (m)	6.9	1.5	0.2	0.2								
Control Delay (s)	11.3	11.6	1.7	0.6								
Lane LOS	B	B	A	A								
Approach Delay (s)	11.3	11.6	1.7	0.6								
Approach LOS	B	B										
Intersection Summary												
Average Delay			5.6									
Intersection Capacity Utilization		30.3%		ICU Level of Service				A				
Analysis Period (min)			15									

HCM Unsignalized Intersection Capacity Analysis
13: Mississauga Road & The Grange Side Road

Existing Traffic
AM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	0	1	13	9	6	1	1	36	5	4	183	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	0	1	13	9	6	1	1	36	5	4	183	0
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	236	234	183	245	232	38	183			41		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	236	234	183	245	232	38	183			41		
tC, single (s)	7.1	6.5	6.3	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.4	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	98	99	99	100	100			100		
cM capacity (veh/h)	716	668	844	699	670	1039	1404			1581		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	14	16	42	187								
Volume Left	0	9	1	4								
Volume Right	13	1	5	0								
cSH	829	702	1404	1581								
Volume to Capacity	0.02	0.02	0.00	0.00								
Queue Length 95th (m)	0.4	0.5	0.0	0.1								
Control Delay (s)	9.4	10.2	0.2	0.2								
Lane LOS	A	B	A	A								
Approach Delay (s)	9.4	10.2	0.2	0.2								
Approach LOS	A	B										
Intersection Summary												
Average Delay			1.3									
Intersection Capacity Utilization		25.7%		ICU Level of Service				A				
Analysis Period (min)		15										

HCM Unsignalized Intersection Capacity Analysis
14: Mississauga Road & Woodland Court

Existing Traffic
AM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	10	1	25	1	0	192
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	10	1	25	1	0	192
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None		None	
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	218	26		26		
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	218	26		26		
tC, single (s)	6.4	6.2		4.1		
tC, 2 stage (s)						
tF (s)	3.5	3.3		2.2		
p0 queue free %	99	100		100		
cM capacity (veh/h)	775	1056		1601		
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	11	26	192			
Volume Left	10	0	0			
Volume Right	1	1	0			
cSH	794	1700	1601			
Volume to Capacity	0.01	0.02	0.00			
Queue Length 95th (m)	0.3	0.0	0.0			
Control Delay (s)	9.6	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	9.6	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			0.5			
Intersection Capacity Utilization		20.1%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
15: Mississauga Road & Caledon Mountain Dr

Existing Traffic
AM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	1	2	47	2	1	193
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	1	2	47	2	1	193
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None		None	
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	243	48		49		
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	243	48		49		
tC, single (s)	6.4	6.2		4.1		
tC, 2 stage (s)						
tF (s)	3.5	3.3		2.2		
p0 queue free %	100	100		100		
cM capacity (veh/h)	749	1027		1571		
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	3	49	194			
Volume Left	1	0	1			
Volume Right	2	2	0			
cSH	914	1700	1571			
Volume to Capacity	0.00	0.03	0.00			
Queue Length 95th (m)	0.1	0.0	0.0			
Control Delay (s)	9.0	0.0	0.0			
Lane LOS	A		A			
Approach Delay (s)	9.0	0.0	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay		0.1				
Intersection Capacity Utilization		21.0%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
16: Mississauga Road & Bush Street/Coffee Shop Access

Existing Traffic
AM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Sign Control		Stop			Stop			Stop			Stop	
Volume (vph)	7	1	135	5	2	4	28	5	3	4	52	5
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	7	1	135	5	2	4	28	5	3	4	52	5
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	143	11	36	61								
Volume Left (vph)	7	5	28	4								
Volume Right (vph)	135	4	3	5								
Hadj (s)	-0.53	-0.13	0.25	-0.04								
Departure Headway (s)	3.6	4.1	4.5	4.2								
Degree Utilization, x	0.14	0.01	0.05	0.07								
Capacity (veh/h)	970	842	762	823								
Control Delay (s)	7.2	7.2	7.7	7.5								
Approach Delay (s)	7.2	7.2	7.7	7.5								
Approach LOS	A	A	A	A								
Intersection Summary												
Delay					7.4							
HCM Level of Service					A							
Intersection Capacity Utilization			24.2%			ICU Level of Service				A		
Analysis Period (min)				15								

HCM Unsignalized Intersection Capacity Analysis
1: Winston Churchill Boulevard & Olde Base Line Road

Existing Traffic
PM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	20	146	45	15	62	22
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	20	146	45	15	62	22
Pedestrians	1		1			
Lane Width (m)	3.7		3.7			
Walking Speed (m/s)	1.2		1.2			
Percent Blockage	0		0			
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	200	54			61	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	200	54			61	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	97	86			96	
cM capacity (veh/h)	760	1013			1554	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	166	60	84			
Volume Left	20	0	62			
Volume Right	146	15	0			
cSH	974	1700	1554			
Volume to Capacity	0.17	0.04	0.04			
Queue Length 95th (m)	4.3	0.0	0.9			
Control Delay (s)	9.5	0.0	5.6			
Lane LOS	A		A			
Approach Delay (s)	9.5	0.0	5.6			
Approach LOS	A					
Intersection Summary						
Average Delay			6.6			
Intersection Capacity Utilization		28.0%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
2: Winston Churchill Boulevard & Sideroad 5

Existing Traffic
PM Peak Hour

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Volume (veh/h)	4	21	50	132	56	5
Sign Control	Stop			Free	Free	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	4	21	50	132	56	5
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type				None	None	
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	290	58	61			
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	290	58	61			
tC, single (s)	6.4	6.2	4.1			
tC, 2 stage (s)						
tF (s)	3.5	3.3	2.2			
p0 queue free %	99	98	97			
cM capacity (veh/h)	682	999	1555			
Direction, Lane #	EB 1	NB 1	SB 1			
Volume Total	25	182	61			
Volume Left	4	50	0			
Volume Right	21	0	5			
cSH	930	1555	1700			
Volume to Capacity	0.03	0.03	0.04			
Queue Length 95th (m)	0.6	0.7	0.0			
Control Delay (s)	9.0	2.2	0.0			
Lane LOS	A	A				
Approach Delay (s)	9.0	2.2	0.0			
Approach LOS	A					
Intersection Summary						
Average Delay			2.3			
Intersection Capacity Utilization		26.4%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
3: Winston Churchill Boulevard & The Grange Side Road

Existing Traffic
PM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	5	13	145	4	6	55
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	5	13	145	4	6	55
Pedestrians	1					1
Lane Width (m)	3.7					3.7
Walking Speed (m/s)	1.2					1.2
Percent Blockage	0					0
Right turn flare (veh)						
Median type			None			None
Median storage veh						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	215	149			150	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	215	149			150	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	99	99			100	
cM capacity (veh/h)	774	901			1442	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	18	149	61			
Volume Left	5	0	6			
Volume Right	13	4	0			
cSH	862	1700	1442			
Volume to Capacity	0.02	0.09	0.00			
Queue Length 95th (m)	0.4	0.0	0.1			
Control Delay (s)	9.3	0.0	0.8			
Lane LOS	A		A			
Approach Delay (s)	9.3	0.0	0.8			
Approach LOS	A					
Intersection Summary						
Average Delay			0.9			
Intersection Capacity Utilization		18.4%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
4: Winston Churchill Blvd & Bush Street

Existing Traffic
PM Peak Hour



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑ ↗			↖ ↘	↖ ↗	
Volume (veh/h)	54	58	2	132	148	6
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	54	58	2	132	148	6
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None		None			
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume		112		219	83	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol		112		219	83	
tC, single (s)		4.1		6.4	6.2	
tC, 2 stage (s)						
tF (s)		2.2		3.5	3.3	
p0 queue free %		100		81	99	
cM capacity (veh/h)		1490		770	982	
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	112	134	154			
Volume Left	0	2	148			
Volume Right	58	0	6			
cSH	1700	1490	777			
Volume to Capacity	0.07	0.00	0.20			
Queue Length 95th (m)	0.0	0.0	5.1			
Control Delay (s)	0.0	0.1	10.8			
Lane LOS		A	B			
Approach Delay (s)	0.0	0.1	10.8			
Approach LOS			B			
Intersection Summary						
Average Delay			4.2			
Intersection Capacity Utilization		23.8%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
5: Olde Base Line Road & Shaws Creek Road

Existing Traffic
PM Peak Hour

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Volume (veh/h)	4	73	167	7	6	2
Sign Control	Free	Free			Stop	
Grade	0%	0%			0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	4	73	167	7	6	2
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None	None				
Median storage (veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	174			252	170	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	174			252	170	
tC, single (s)	4.3			6.4	6.2	
tC, 2 stage (s)						
tF (s)	2.4			3.5	3.3	
p0 queue free %	100			99	100	
cM capacity (veh/h)	1275			739	879	
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	77	174	8			
Volume Left	4	0	6			
Volume Right	0	7	2			
cSH	1275	1700	770			
Volume to Capacity	0.00	0.10	0.01			
Queue Length 95th (m)	0.1	0.0	0.2			
Control Delay (s)	0.4	0.0	9.7			
Lane LOS	A		A			
Approach Delay (s)	0.4	0.0	9.7			
Approach LOS			A			
Intersection Summary						
Average Delay		0.4				
Intersection Capacity Utilization		19.2%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
6: Rockside Road & Olde Base Line Road

Existing Traffic
PM Peak Hour



Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	↑→	↓→	↑←	↓←	↑↖	↓↖
Volume (veh/h)	62	0	4	176	0	2
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	62	0	4	176	0	2
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume		62		246		62
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol		62		246		62
tC, single (s)		4.1		6.4		7.2
tC, 2 stage (s)						
tF (s)		2.2		3.5		4.2
p0 queue free %		100		100		100
cM capacity (veh/h)		1554		745		785
Direction, Lane #	EB 1	WB 1	NB 1			
Volume Total	62	180	2			
Volume Left	0	4	0			
Volume Right	0	0	2			
cSH	1700	1554	785			
Volume to Capacity	0.04	0.00	0.00			
Queue Length 95th (m)	0.0	0.1	0.1			
Control Delay (s)	0.0	0.2	9.6			
Lane LOS		A	A			
Approach Delay (s)	0.0	0.2	9.6			
Approach LOS		A				
Intersection Summary						
Average Delay		0.2				
Intersection Capacity Utilization		22.5%		ICU Level of Service		A
Analysis Period (min)		15				

HCM Unsignalized Intersection Capacity Analysis
7: Mississauga Road & Olde Base Line Road

Existing Traffic
PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	1	27	35	5	46	21	102	178	16	12	67	2
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	1	27	35	5	46	21	102	178	16	12	67	2
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	526	490	68	530	483	186	69			194		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	526	490	68	530	483	186	69			194		
tC, single (s)	8.1	6.5	6.3	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	4.4	4.0	3.4	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	94	96	99	90	98	93			99		
cM capacity (veh/h)	288	446	979	401	450	861	1538			1391		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	63	72	296	81								
Volume Left	1	5	102	12								
Volume Right	35	21	16	2								
cSH	631	518	1538	1391								
Volume to Capacity	0.10	0.14	0.07	0.01								
Queue Length 95th (m)	2.3	3.4	1.5	0.2								
Control Delay (s)	11.3	13.1	3.0	1.2								
Lane LOS	B	B	A	A								
Approach Delay (s)	11.3	13.1	3.0	1.2								
Approach LOS	B	B										
Intersection Summary												
Average Delay			5.1									
Intersection Capacity Utilization		36.0%		ICU Level of Service				A				
Analysis Period (min)			15									

HCM Unsignalized Intersection Capacity Analysis
13: Mississauga Road & The Grange Side Road

Existing Traffic
PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Volume (veh/h)	1	4	7	4	4	4	12	228	3	5	66	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	1	4	7	4	4	4	12	228	3	5	66	0
Pedestrians		1									1	
Lane Width (m)		3.7									3.7	
Walking Speed (m/s)		1.2									1.2	
Percent Blockage		0									0	
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	338	332	67	338	330	230	67				231	
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	338	332	67	338	330	230	67				231	
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.2				4.5	
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.3				2.6	
p0 queue free %	100	99	99	99	99	100	99				100	
cM capacity (veh/h)	607	583	1001	605	584	813	1496				1142	
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	12	12	243	71								
Volume Left	1	4	12	5								
Volume Right	7	4	3	0								
cSH	774	653	1496	1142								
Volume to Capacity	0.02	0.02	0.01	0.00								
Queue Length 95th (m)	0.3	0.4	0.2	0.1								
Control Delay (s)	9.7	10.6	0.4	0.6								
Lane LOS	A	B	A	A								
Approach Delay (s)	9.7	10.6	0.4	0.6								
Approach LOS	A	B										
Intersection Summary												
Average Delay			1.2									
Intersection Capacity Utilization		25.8%		ICU Level of Service				A				
Analysis Period (min)		15										

HCM Unsignalized Intersection Capacity Analysis
14: Mississauga Road & Woodland Court

Existing Traffic
PM Peak Hour



Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	4	1	223	7	2	68
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	4	1	223	7	2	68
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	298	226		230		
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	298	226		230		
tC, single (s)	6.4	6.2		4.1		
tC, 2 stage (s)						
tF (s)	3.5	3.3		2.2		
p0 queue free %	99	100		100		
cM capacity (veh/h)	696	818		1350		
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	5	230	70			
Volume Left	4	0	2			
Volume Right	1	7	0			
cSH	717	1700	1350			
Volume to Capacity	0.01	0.14	0.00			
Queue Length 95th (m)	0.1	0.0	0.0			
Control Delay (s)	10.1	0.0	0.2			
Lane LOS	B		A			
Approach Delay (s)	10.1	0.0	0.2			
Approach LOS	B					
Intersection Summary						
Average Delay			0.2			
Intersection Capacity Utilization		22.2%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
15: Mississauga Road & Caledon Mountain Dr

Existing Traffic
PM Peak Hour

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Volume (veh/h)	3	1	200	3	4	71
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	3	1	200	3	4	71
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	280	202		203		
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	280	202		203		
tC, single (s)	6.4	6.2		4.1		
tC, 2 stage (s)						
tF (s)	3.5	3.3		2.2		
p0 queue free %	100	100		100		
cM capacity (veh/h)	712	844		1381		
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	4	203	75			
Volume Left	3	0	4			
Volume Right	1	3	0			
cSH	741	1700	1381			
Volume to Capacity	0.01	0.12	0.00			
Queue Length 95th (m)	0.1	0.0	0.1			
Control Delay (s)	9.9	0.0	0.4			
Lane LOS	A		A			
Approach Delay (s)	9.9	0.0	0.4			
Approach LOS	A					
Intersection Summary						
Average Delay			0.3			
Intersection Capacity Utilization		20.7%		ICU Level of Service		A
Analysis Period (min)			15			

HCM Unsignalized Intersection Capacity Analysis
16: Mississauga Road & Bush Street/Coffee Shop Access

Existing Traffic
PM Peak Hour

Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Sign Control		Stop			Stop			Stop			Stop	
Volume (vph)	13	2	52	2	1	1	152	61	3	2	22	20
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Hourly flow rate (vph)	13	2	52	2	1	1	152	61	3	2	22	20
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	67	4	216	44								
Volume Left (vph)	13	2	152	2								
Volume Right (vph)	52	1	3	20								
Hadj (s)	-0.38	-0.05	0.14	-0.23								
Departure Headway (s)	4.1	4.5	4.2	4.0								
Degree Utilization, x	0.08	0.01	0.25	0.05								
Capacity (veh/h)	824	739	828	862								
Control Delay (s)	7.4	7.5	8.7	7.3								
Approach Delay (s)	7.4	7.5	8.7	7.3								
Approach LOS	A	A	A	A								
Intersection Summary												
Delay					8.2							
HCM Level of Service					A							
Intersection Capacity Utilization				29.3%		ICU Level of Service						A
Analysis Period (min)					15							