



**NOTES**

1. THIS DRAWING MUST BE USED IN CONJUNCTION WITH 5-2-11, 5-2-16A, 5-2-16B, 5-2-16D, 5-2-16E AND 5-2-16F
2. THIS DRAWING SHALL BE USED AS A REGIONAL STANDARD AND ANY FIELD ADJUSTMENTS OR REVISIONS REQUIRE REGIONAL APPROVAL
3. TACTILE WALKING SURFACE INDICATORS SHALL BE INSTALLED AT ALL PEDESTRIAN CROSSINGS IN CONJUNCTION WITH ALL ROAD AND SIDEWALK CONSTRUCTION, RECONSTRUCTION AND RESURFACING PROJECTS
4. THE FIRST STEP FROM THE CURB SHALL NOT LAND ON A LADDER MARKER

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.



**PUBLIC WORKS  
STANDARD DRAWING**

REV. DATE: JUNE 2017

APPROVED BY

DRAWN BY

G.K./S.L.

G.K.

STD. DWG. NUMBER

SCALE

**5-2-16C**

N.T.S.

**SIGNALIZED INTERSECTION CONFIGURATIONS  
OF PEDESTRIAN CROSSINGS**